ECOPLANT SUN TRACING SOLAR



ŔŔ



www.ecoplant.solar

Visual energy





Solar & grid power in one

Charger

Easy energy refuel

Nano coat

Self cleaning



Bright light emitted diodes

Warranty

Full operational warranty

Safety

Safe HE batteries, no fire

Coolback

Patented backside for special cooling

LiFePo4

Five years warranty max 6000 cycles

Easy

Installation within 2 hours

Insurance

Low cost, full coverage



Instant data control



Effectively use of fexible energy

Bi-facial power

0





24 patents



EV-charger



Albedo efficiency possible

+/+ 40%

Suntracing efficiency Optimal solar harvest



Easy nano clean solar panel



Natural temperature control

Ecoplant efficiency



Circular solar





Promote your brand



Solutions

Complete service enhances operation efficiency



Onsite service

Technician support



Online service

24/7 available





Service and efficiency control during operating





Available control app for active interaction



HEXAGON 2000



Features HEXAGON 2000

Power Upto 2500 kWh



Remote service control



-40 °C~55 °C





Resistant up to 27 m/s



Bi-facial Albedo technology



Natural climate control



Salt erosion resistant



Suntracing efficiency



HEXAGON 3000



Features HEXAGON 3000

Upto 4000 kWh

GPS/GSM

Remote service control

Height MAX 4.6M @ 55° MIN 2.4M @ 10' -40 °C~55 °C





Resistant up to 27 m/s

+/+ 5%

Encapsulation technology



Natural climate control



Suntracing efficiency



Salt erosion resistant



HEXAGON 4000



Features HEXAGON 4000

Power Upto 5000 kWh GPS/GSM

Remote service control

Height MAX 4.6M @ 55* MIN 2.4M @ 10* -40 °C~55 °C Working temperature





Resistant up to 27 m/s



Bi-facial Albedo technology

+/+ 40%



Natural climate control



Salt erosion resistant



OCTAGON 8000



Features OCTAGON 8000

Power Upto 7000 kWh



Remote service control

Height MAX 5M @ 55* MIN 3M @ 10* -40 °C~55 °C





Resistant up to 27 m/s



Bi-Facial TOPCon solar Albedo technology

+/+ 40%



Natural climate control



Salt erosion resistant

Passion & LifePower









www.homebattery.energy

Battery features

LiFePo4

Single unit 5.12 kWh/43.6 KG



Incl. Battery management system

Nominal Capacity

51.2V - 100Ah

Operation Voltage

40 V - 58.4 V

Lifecycle

Five years warranty max 6000 cycles

-5 °C~35 °C

Working temperature (dis)charge

Communication

Can. RS485

(Dis)charge

Charge 100A Pulse discharge current 300A

IP65 UN38.3





Non tracing solar



Solarsol 600

6 Bi-Facial panels Easy add accesoires Micro inverter 1000W Easy self connection to the grid Saving up to 13% on energy per month

Solarsol 1200

8 Bi-Facial panels Easy add accesoires Micro inverter 1000W Easy self connection to the grid Saving up to 26% on energy per month





Ecoplant features



Festivals & events

FESTIPLANT

www.festiplant.solar

Learning & doing

SECOPLANT

student.ecoplant.solar



International partners

eleration Academy Day Travel bld Ho

ANY PACE

1





www.ecoplant.solar





www.ecoplant.solar